

Great Stuff™ Pro B1

Polyurethane Foam Sealant

FEATURES

Description

Great Stuff™ Pro* is a moisture-curing one-component polyurethane gun foam sealant. It contains an environmentally safe propellant, which complies with the latest EU regulations banning all CFC- and HCFC-propellants. Great Stuff™ Pro is a foam sealant, which can be used at temperatures being from +18°C to +35°C, the optimal processing temperatures being from 18°C to 25°C.

Ease of use

Once fully set, the foam can be trimmed, cut, sanded, painted or plastered over. Great Stuff™ Pro is used to fill holes, gaps, cracks and cavities within various building materials. It seals voids and connection joints between different building materials. It is also meant to reduce and control air-leakage in the building envelop and thereby sound transmission. It's an aid to mechanically fixing and insulating door and window frames. Also for air sealing and stabilizing pipe entries through brickwork and other walls.

INSTALLATION

Application

Prior to spraying the foam, surfaces must be dry, firm, clean and free of dust, grease or loose particles. The foam adheres well to most common building materials like wood, concrete, render, plaster board, metal, mineral wool, XPS, EPS, PUR and PIR foam. An exemption are polyethylene or other polyolefin foils as well as silicone, oil or grease contaminated surfaces.

How to Apply the Product

1. Shake the can vigorously at least 20 times.
2. Screw the gun onto the valve.
3. Open the dosing knob at the rear of the gun dispenser.
4. To extrude the foam, make sure the can is in an upright position with the valve down, carefully pull the gun trigger.
5. Discard the first 10 – 20g of a fresh can.
6. The applied amount can be dosed by pulling the trigger or the dosing knob at the back of the gun

Curing

The foam cures quickly. Cured foam can only be removed mechanically. Fresh foam remains can be removed with the Great Stuff™ Pro Foam Cleaner*.

Equipment

If the can is empty just connect a new one, if needed clean the gun valve and tip. During short interruptions for a couple of hours or a day, leave the can connected to the gun. Only close the dosing knob at the back. During long interruptions i.e. days or weeks detach the gun from the can and clean both using the Great Stuff™ Pro Foam Cleaner. For best possible performance and foam quality we recommend the use of DuPont recommended accessories.

Available Accessories

Great Stuff™ Pro Gun* (GMID 99057360)
Great Stuff™ Eco Gun* (GMID 308917)
Great Stuff™ Pro Foam Cleaner (GMID 357500)

PROPERTIES

Typical Product Properties ¹⁾	Unit	Great Stuff™ Pro B1 Gun Foam Sealant	Great Stuff™ Pro B1 Dual ²⁾ Foam Sealant	Test method
Color	–	Pink	Pink	Visual
Cut time	min	20	20 (gun) / 30 (straw)	EN17333-3 M1
Tack free time	min	10	10 (gun) / 15 (straw)	EN17333-3 M2
Reaction to fire	–	B1	B1	DIN4102-1
Reaction to fire	–	B-s1-d0	B-s1-d0	EN13501-1

1) Test results obtained on the basis of test methods referred in the above.

2) With the dual version, the foam can be applied either with a straw or with a gun.

HANDLING

Important

Note that the curing behavior of the foam can change with ambient conditions (temperature and humidity). For fast and homogeneous foam curing humidity is needed, but excessive moistening may negatively affect the bond strength and shall be avoided. The cured foam is resistant to temperatures in the range of -40°C to +100°C. The foam exhibits a high durability, if protected from direct sunlight i.e. UV radiation.

Precautionary Statements

Read and follow the entire Installation and Handling section and the Safety Data Sheets (SDSs, formerly MSDSs or Material Safety Data Sheets) carefully before use. They contain important information on applicable safety regulations and the provisions on the protection of health. Material safety data sheets are revised regularly – please request and note the latest version before using/processing or obtain directly at: www.dupont.com (SDS Finder)

Great Stuff™ Pro foam sealants are very sticky and will adhere to most surfaces and skin. Do not get foam on skin. Cover all skin, wear long sleeves, gloves, and goggles or safety glasses.



Shelf Life and Storage

Store and transport the cans always in an upright position and in dry conditions. Protect the product and accessories from direct sunlight.

Storage temperature: +5°C to +25°C

Shelf life: 18 months

Packaging

Tinplated steel cans 750ml, box of 12 cans each
Great Stuff™ Pro B1 Gun Foam Sealant
Great Stuff™ Pro B1 Dual Foam Sealant

Supplemental Information

Visit www.building.dupont.com or contact a local DuPont representative for more specific instructions.



Specialty Electronic Materials Switzerland GmbH

Grossmatte 4
CH-6014 Luzern
Switzerland

building.dupont.com
or call +800 3876 6838

Specialty Electronic Materials UK Limited

Kings Court, London Road, Stevenage Hertfordshire
SG1 2NG
UNITED KINGDOM

building.dupont.com
or call +800 3876 6838

DuPont encourages its customers to review their application of DuPont products from the standpoint of human health and environmental quality. To help ensure that DuPont products are not used in ways for which they were not intended or tested, DuPont personnel will assist customers in dealing with ecological and product safety considerations. Your DuPont sales representative can arrange the proper contacts.

NOTE: This information corresponds to our current knowledge on the subject. It is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for any application other than the application as specified herein. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liabilities in connection with any use of this information for applications other than the application as specified herein. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. Product safety information is available on request. This data sheet is a printed document and is valid without signature.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc., unless otherwise noted.
© 2024 DuPont

Sept 2024
B28-291-95525-0924